THE UNITS ARE DESIGNED TO WORK WITH UNSTABLE SUPPLY VOLTAGES CAUSED BY GENERATORS AND LONG EXTENSION LEADS.

ABLE TO MEET THE REQUIREMENTS OF EVEN THE MOST DEMANDING USER WITH A WIDE RANGE OF **CURRENTS AND A HIGH DUTY CYCLE.** 

SUITABLE FOR ALL TYPES OF COMMERCIAL ELECTRODES, RUTILE, STAINLESS STEEL, MILD STEEL. THE TIG/MMA SWITCH ALSO ENABLES THE USE FOR TIG WELDING STARTING FROM A SCRATCH ARC.

**ACCESSORIES SOLD SEPARATELY** 


## **GLOBUS 150**

Supply Voltage: 240 Volt Single Phase 15 Amp Current Range DC : 15 - 140 Amps

Duty Cycle : 60% @ 140 Amps / 100% @ 110 Amps

No Load Voltage 90 Volts DC

Dimensions : (W x L x H) 155 x 360 x 320 mm Weight: 7.3 KG







## **GLOBUS 170**

Supply Voltage: 240 Volt Single Phase 15 Amp Current Range DC: 15 ~ 170 Amps Duty Cycle: 50% @ 160 Amps / 100% @ 115 Amps No Load Voltage: 90 Volts DC Dimensions: (WxLxH) 155 x 360 x 320 mm Weight : 8.0 KG Electrode Size : ARC 4.0 mm / TIG 3.2 mm



NERTERIO

## Accessories















AR101

EH20

**EH31** 

EL20

EL31

INV20KIT

**INV31KIT** 

Supplied By:

